




business hardware solutions

Datasheet

TRUSTER® EX4605



De ce să aleg un server **TRUSTER®** ?

- Sunt realizate pe platforme cu chipset **Intel®**, ce și-au dovedit de-a lungul timpului calitatea și stabilitatea în funcționare
- Mai mult, folosesc numai componente testate și certificate
- Toate serverele **TRUSTER®** sunt produse sub standardul de calitate **ISO 9001**
- Beneficiază de suport tehnic în perioada de garanție și postgaranție
- Pot beneficia de **service onsite** pe bază de contract sau la cerere

Server-ul **TRUSTER®** EX4605 este echipat cu noua generație de procesoare Intel seria E5-46xx și înglobează cele mai noi tehnologii disponibile pentru soluțiile database / application servers. Asigură puterea de calcul și disponibilitatea necesare unui mediu de calcul din marilor companii sau instituții guvernamentale.



Facilități și beneficii:

- putere de calcul – pana la 4 procesoare Intel E5-46xx
- pana la 10 HDD SAS/SATA 3.5" / 2.5";
- conectivitate – dual 10 Gigabit; Fiber channel / SAS / Infiniband (optional)
- capabilitati RAID intern; extern (optional)
- alimentare redundanta
- remote management / dedicated port

S.C. PRO SYS S.R.L.

Bd. Pache Protopopescu nr. 108, sector 2, București
Tel: +40-21-252 42 32, e-mail: office@prosys.ro, www.prosys.ro



TRUSTER® EX4605

Cod: DS-EX4605-Rev.01X1309	
Procesoare	Pana la patru Intel® Xeon® processor E5-46xx
Platforma	Model: SM X9QR7-TF+
	QPI: up to 8 GT/s
	Chipset: Intel® C602
	Integrated LAN: 2 x 10 Gigabit Ethernet Intel X540 Controller / 1 x IPMI 2.0 w/ dedicated connector
Memorie	1GB, 2GB, 4GB, 8GB, 16, 32GB modules; 1600 / 1333 / 1066MHz ECC Registered
	Support up to 1024GB 1333 / 1066 / 800MHz DDR3 ECC Registered memory
Sisteme de operare suportate	Windows 2008 Server x64; Windows 2008 Server x64 R2; Windows Server 2012
	RedHat Linux EL 5.7; 6.2; 6.3; SuSE Linux 10; 11; CentOS 6.3; Solaris 10; 11, OpenIndiana, XenServer
Interfete	USB 2.0: 4 x Back, 2 x Front
	Serial: 1 x 9 pin RS232;
	Integrated LAN: 2 x RJ45 for network; 1 x RJ45 management port
	Graphics: 1 x VGA back
	FC / SAS / SCSI / IB Optional
RAID	SAS 6Gbps RAID 0, 1, 5, 6, 10, 50, 60; 1GB memory cache, optional BBU
Video	Onboard
IPMI	Support for Intelligent Platform Management Interface 2.0
HDDs	Hot-swap SAS / SATA backplane: standard up to 5 3.5"/ 2.5" HDDs; SAS 300, 450, 600GB 10000rpm and 15000rpm
	Or up to 5 3.5"/2.5" HDD SATA-III 250, 500, 1000, 2000, 3000, 4000GB 7200 / 10000 rpm
	Option for Hot-swap backplane add-on kit to support up to 10 3.5"/2.5" bays
Carcasa	4U rackmount
	Up to 10 x 3.5"/2.5" HDD hot-swap bays (optional backplane add-on kit); Up to 3 x 5.25" bays
	USB: 4 x Rear, 2 x Front
	Power supply 1400W module, redundant 1+1 w/ PFC, hot-swap; 100-240V, 50-60Hz, 15A max.
Accesorii	Manual, CD drivers, rack mounting kit